

LED 7 Watt MR16: GU5.3 and PAR16

Features and Benefits

- 7 Watt Low Power and High Performance
- Up to 85% less energy than
- Smooth, uniform dimming
- Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
- Track or down light installations are not strained by excess weight
- Shatter resistant
- Rated Lifetime: 25,000 hours
- 5 Year Warranty*
- UV, IR and Mercury-free
- UL-Dry Location



**5 Year
Warranty**

**Reduces
Energy & Cost**

**No Lead or
Mercury**

Color Temperature(CCTK):	Part Number:	Description:	Lumens:	CBCP:	CRI:	CCT:	Beam Angle:	Voltage:
2400K	12V MR16 GU5.3							
	LED712VMR1624KNFL	Dimmable 7W MR16 GU5.3	500	TBD	82	2400	20°	12 VAC
	LED712VMR1624KFL	Dimmable 7W MR16 GU5.3	500	TBD	82	2400	40°	12 VAC
	120V PAR16							
	LED7P1624KNFL	Dimmable 7W PAR16	500	TBD	82	2400	20°	120V
	LED7P1624KFL	Dimmable 7W PAR16	500	TBD	82	2400	40°	120V

Voltage:	Operating Frequency:	Operating Temperature:	Life Hours:	Dimensions (in inches):	Case Quantity:	Indoor/Outdoor:	Certified Installer Required:
120 VAC	50/60 Hz	-40 °C to 50 °C	25,000	2" x 2" 2" x 3"	12	Indoor	No



Applications

- Display Lights
- Recessed Downlights
- Track Lights
- Hotels
- Casinos
- Restaurants
- Commercial Buildings
- Residential
- Theaters
- Outdoor fixtures that protect from elements

Certifications:
RoHS, ETL Listed



LED 7 Watt MR16: GU5.3 and PAR16

Color Temperature(CCTK):	Part Number:	Description:	Lumens:	CBCP:	CRI:	CCT:	Beam Angle:	Voltage:
2700K	12V MR16 GU5.3							
	LED712VMR1627KNFL	Dimmable 7W MR16 GU5.3	500	3296	82	2700	20°	12 VAC
	LED712VMR1627KFL	Dimmable 7W MR16 GU5.3	500	1057	82	2700	40°	12 VAC
	120V PAR16							
	LED7P1627KNFL	Dimmable 7W PAR16	500	3296	82	2700	20°	120V
	LED7P1627KFL	Dimmable 7W PAR16	500	1057	82	2700	40°	120V

3000K	12V MR16 GU5.3							
	LED712VMR1630KNFL	Dimmable 7W MR16 GU5.3	525	3296	82	3000	20°	12 VAC
	LED712VMR1630KFL	Dimmable 7W MR16 GU5.3	525	1057	82	3000	40°	12 VAC
	120V PAR16							
	LED7P1630KNFL	Dimmable 7W PAR16	525	3296	82	3000	20°	120V
	LED7P1630KFL	Dimmable 7W PAR16	525	1057	82	3000	40°	120V

4100K	12V MR16 GU5.3							
	LED712VMR1641KNFL	Dimmable 7W MR16 GU5.3	550	3296	82	4100	20°	12 VAC
	LED712VMR1641KFL	Dimmable 7W MR16 GU5.3	550	1057	82	4100	40°	12 VAC
	120V PAR16							
	LED7P1641KNFL	Dimmable 7W PAR16	550	3296	82	4100	20°	120V
	LED7P1641KFL	Dimmable 7W PAR16	550	1057	82	4100	40°	120V

